

BeyondVoice™

Phone System Interface Options

	Analog	Digital – T-1 CAS	Digital – PRI
Number of Lines Supported	5 – 14 lines BeyondVoice™ I 15 – 24 lines BeyondVoice™ II	9 – 14 lines BeyondVoice™ I 15 – 24 lines BeyondVoice™ II 36 – 48 lines BeyondVoice™ III	9 – 14 lines BeyondVoice™ I 15 – 23 lines BeyondVoice™ II 35 – 46 lines BeyondVoice™ III
Caller ID Options/ Availability	Name & Number	None	Name & Number
Account Code Availability	Yes	Yes	No
Availability of Other Features	Yes	No, phone system provides features	No, phone system provides features
DID (Direct Inward Dial)	No	Yes	Yes
Hunt Group/ Trunk Group Options	Hunting Provided	Standard: One Combo trunk	Only 1 Combo trunk group
Phone Number Level Billing	Yes	No	No
Installation Interval	30-45 Days (60 days if more than 17 phone lines)	30-45 Days BeyondVoice™ III – 60 Days	60 Days
Outbound Caller ID Display	One Number/ Line	One Number/ Trunk Group	Depends on PBX configuration*

*PBX must be set to send 10 digits.

CAS = Channel Associated Signaling **PRI** = Primary Rate Interface

